



Houston Office
248 McCarty Dr.
P.O. Box 15214
Houston TX, 77220-5214
(713) 672-8251
Fax (713) 672-6336
Email clemtex@clemtex.com

1-800-CLEMTEX
www.clemtex.com

Corpus Christi Branch
4750 Westway
P.O. Box 5036
Corpus Christi, TX 78465
(361) 882-8282
Fax (361) 882-6029

Dallas Branch
4770 Gretna
Dallas, TX 75207
(214) 631-0584
Fax (214) 631-5824
1-800-BLAST 97

Blast-It-All – ABC Shot Peener



Model Number	Description	Floor Area (W)	Required (D)
ABC 3636P	Cabinet Only, less Blower & DC *	108"	67"
ABC 3636P - 400DB	400 CFM Blower with Dust Bag	108"	88"
ABC 3636P - D10	700 CFM Blower with D-10 DC	108"	108"
ABC 3636P - M2DC	700 CFM Blower with M2 DC	108"	108"
ABC 4836P	Cabinet Only, less Blower & DC *	112"	67"
ABC 4836P - 400DB	400 CFM Blower with Dust Bag	112"	88"
ABC 4836P - D10	700 CFM Blower with D-10 DC	112"	108"
ABC 4836P - M2DC	700 CFM Blower with M2 DC	112"	108"
ABC 6036P	Cabinet Only, less Blower & DC *	120"	67"
ABC 6036P - 400DB	400 CFM Blower with Dust Bag	120"	88"
ABC 6036P - D10	700 CFM Blower with D-10 DC	120"	108"
ABC 6036P - M2DC	700 CFM Blower with M2 DC	120"	108"

Technical Specifications

Cabinet Construction

- 14 gauge reinforced continuously welded

Finish

- Durable enamel
- Primed and painted. Corrosion resistant

Working Chamber

- ABC 3636P - 36" W x 36" D
- ABC 4836P – 48" W x 36" D
- ABC 6036P – 60" W x 36" D
- Safety door interlocks
- Self adjusting door latches
- Full length hinges

Viewing Window

- 12½" H x 21" W
- Quick change, square cornered
- Tempered glass

Lighting

- Two tube, 24" fluorescent fixture
- Low temperature
- Shielded, externally located
- 120V, 60 Hz

Gloves

- Abrasive resistant, cloth-lined
- 8" padded arm hold ports
- Static resistant gauntlet

Hoses

- ½" I.D. lightweight, flexible, abrasive resistant

Blow-Off Gun

- Fingertip control blow-off nozzle

Pressure Pot

- ASME coded, one cu. ft. capacity
- Air pressure, remote controlled
- Automatic refilling pot
- Heavy duty screen drawer

- ¾" piping
- Adjustable media valve
- Automatic blow down
- Moisture separator

Blasting Nozzle

- Tungsten carbide, ¼" standard

Dust Collector Specifications

D10 Pull Through

- 700 CFM
- 42" W x 25" D x 80" H
- 1 HP motor – 25 dust bags
- Manual pneumatic bag shaker

RPJ2 / DC Drawer

- 5' 10" x 2' 6" x 7' 9"
- 2 – 36" cartridges
- Automatic reverse
- Pulse cleaning

RPJ2H / DC Hopper

- 5' 10" x 2' 6" x 12'
- 2 – 36" cartridges
- Automatic reverse
- Pulse cleaning

Dust Bag

- 1 bag with 400 CFM blower
- Zipper bottom
- 100% cotton sateen

Air (approx. requirements) CFM	40 PSI	60 PSI	80 PSI
3/16" Nozzle	21	32	41
1/4" Nozzle	41	56	72
5/16" Nozzle	64	88	113